

RELIABILITY MONITOR REPORT
FOR

Cartridge Package

Dallas Semiconductor

4401 South Beltwood Parkway
Dallas, TX 75244-3292

This Report was prepared by
Dallas Semiconductor Reliability Engineering

Summary:

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The assemblies covered by this package monitor are:

ASSY SITE	PINS	PACKAGE		
Consonic C	3	Cartridge	Consonic T	3 Cartridge
Dallas	0	Cartridge	Dallas	3 Cartridge
Fastech	2	Cartridge	Fastech	3 Cartridge
Fastech	2	Cartridge (Pb-Free)	Fastech	2 Cartridge w/Chip on Board
Fastech	2	Cartridge w/Flip Chip	Hana	2 Cartridge w/Chip on Board

Note: Due to the nature of the construction on this assembly, there is no operating life data collected

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between 04/01/2005 and 03/31/2006 .

Assembly Information:

Package Type: Cartridge
 Flammability: UL 94-V0
 Moisture Sensitivity (JEDEC J-STD20A) NA
 Date Code Range: 0511 to 0511

STORAGE LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	0511	DS29020	85 C	336 HRS	77	0	
Total:						0	

TEMPERATURE CYCLE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
TEMP CYCLE	0511	DS29020	-40 TO 85C	400 CYS	77	0	
Total:						0	

UNBIASED MOISTURE RESISTANCE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
MOISTURE SOAK	0511	DS29020	85 C/85% R.H.	274 HRS	77	0	
Total:						0	